



INVESTOR IN PEOPLE

The Patent Office  
Concept House  
Cardiff Road  
Newport

South Wales  
NP10 8QQ

13 JAN 2005

WIPO

PCT

## PRIORITY DOCUMENT

SUBMITTED OR TRANSMITTED IN  
COMPLIANCE WITH RULE 17.1(a) OR (b)

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.


In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.


Signed

Dated

30 December 2004



Patents Form 1/77

Patents Act 1977  
(Rule 16)
 P01/7700  
 03DEC03-E856853-1 002842  
 P01/7700.0.00-0328003.9
**Request for grant of a patent**

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

The Patent Office

 Cardiff Road  
 Newport  
 South Wales  
 NP9 1RH

3 DEC 2003

## 1. Your reference

P6942GB

## 2. Patent application number

(The Patent Office will fill in this part)

0328003.9

## 3. Full name, address and postcode of the or of each applicant (underlining all surnames)

 Quill International Industries Plc  
 Castle Lane  
 Melbourne  
 Derbyshire, DE73 1DY.

Patents ADP number (if you know it)

08272320001

If the applicant is a corporate body, give the country/state of its incorporation

British Company

## 4. Title of the invention

A Mist-Spraying Apparatus

## 5. Name of your agent (if you have one)

L. J. Bray &amp; Co.

"Address for service" in the United Kingdom to which all correspondence should be sent (including the postmark)

 Raw Holme  
 Midgehole Road  
 HEBDEN BRIDGE  
 West Yorkshire  
 HX7 7AF

Patents ADP number (if you know it)

04054565001

## 6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number

Country

Priority application number  
(if you know it)Date of filing  
(day / month / year)

## 7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application

Date of filing  
(day / month / year)

## 8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer 'Yes' if:

yes

a) any applicant named in part 3 is not an inventor, or

b) there is an inventor who is not named as an applicant, or

c) any named applicant is a corporate body.

See note (d))

Patents Form 1/77

0087849 03-Dec-03 04:04

# Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form

Description 8

Claim(s) 2

Abstract 1

Drawing(s) 2 only

10. If you are also filing any of the following, state how many against each item.

Priority documents

Translations of priority documents

Statement of inventorship and right to grant of a patent (Patents Form 7/77)

Request for preliminary examination and search (Patents Form 9/77)

Request for substantive examination (Patents Form 10/77)

Any other documents (please specify)

11.

I/We request the grant of a patent on the basis of this application.

Signature



Date

03 December 2003

12. Name and daytime telephone number of person to contact in the United Kingdom

Janet Bray - Tel. 01422 844598

## Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

## Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505.
- Write your answers in capital letters using black ink or you may type them.
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- Once you have filled in the form you must remember to sign and date it.
- For details of the fee and ways to pay please contact the Patent Office.

- 1 -

**A MIST-SPRAYING APPARATUS**

The present invention relates to a mist-spraying apparatus primarily but not exclusively for use in an enclosed space.

The aim of the invention is to provide a 'dry' mist which can sanitize exposed surfaces within an enclosed space without wetting them. The applications of such an apparatus are varied but the present invention has been designed primarily for use in the sanitization of exposed surfaces within an enclosed space that may be a storage area, a room or the like. For example, such a space may comprise the interior of goods and delivery vehicles, typically those which are used to transport items such as hospital laundry and the like. When such laundry is transported it is common for the same vehicle to be used to pick up dirty laundry at the same time as delivering clean laundry. In such circumstances, the opportunity for cross-contamination to occur is great. Even when dirty laundry is not housed within the same vehicle interior as clean laundry, the same vehicle is often used to transport both at separate times so that it is still advantageous for a means to be provided that can sanitize the interior of the vehicle between trips.

25

Similar requirements exist in other fields. For example, operating theatres are in constant use and whilst new sterile packs of instruments and linen are used for each patient, the surfaces within the theatre itself are not normally sanitized between operations. As many operations cause spillage of blood and other body fluids, the sanitization of exposed surfaces within the theatre between operations would be highly desirable.

35

Commercial glasshouses and battery hen-houses and the like also need to be sanitized regularly and mist-spraying

- 2 -

apparatus is often used to spray biocides of various kinds within these structures.

In all of these applications it is a desirable requirement that the mist being sprayed reaches all parts of the enclosed space so that every exposed surface within the space can be treated.

It is therefore an object of the present invention to provide a mist spraying apparatus that can be used for sanitizing an enclosed space and that will substantially fulfill the aforesaid requirement.

According to the present invention there is provided a mist spraying apparatus primarily but not exclusively for use in an enclosed space comprising

an air-blowing means with an outlet conduit through which air can be blown into the space and an inlet conduit through which air from within the space can be drawn for blowing through the outlet conduit to circulate within the space;

a spraying means comprising a pump for delivering liquid from a reservoir to an atomizing nozzle for spraying the liquid into the space in the form of an atomized mist, the atomizing nozzle being located within the outlet conduit so that atomized particles emitted by the atomizing nozzle are entrained in the airstream emitted by the air-blowing means and thereby distributed evenly throughout the space; and

a control means for controlling operation of the air-blowing means and the spraying means that is adapted to commence operation of the air-blowing means prior to operation of the atomizing nozzle and to continue operation of the air-blowing means after operation of the nozzle has ceased in order to continue circulation of the air and any atomized particles entrained therein around the space for a predetermined period of time.

- 3 -

Hence, in the present invention the air-blowing means is used to create an airstream in the space which immediately entrains the atomized particles being emitted by the atomizing nozzle. As a result the particles are rapidly diluted but also evenly distributed into the airstream and are thus applied evenly over all exposed surfaces within the space being sprayed. Circulation of the air before the atomizing nozzle's operation ensures that the particles emitted by the nozzle are always entrained as atomized particles and do not clump together to form droplets, which are wetting and tend to fall uselessly to the floor of the space. Likewise, recirculation of the air after operation of the nozzle has ceased ensures that all surfaces within the space are reached by the airstream. It will be appreciated that the length of time that the nozzle operates and that the air is recirculated after nozzle operation has ceased will depend on the nature and concentration of the liquid being sprayed, the size of the enclosed space and the particular application of the apparatus and can be varied as required.

Preferably, the atomizing nozzle is located centrally within the outlet conduit.

Preferably also, the outlet conduit has a rectangular cross-sectional profile.

Preferably also, the outlet conduit defines a slot so that the airstream emitted into the space is in the form of a slot-jet.

Preferably also, the atomizing nozzle is inset within the outlet conduit.

- 4 -

Preferably also, the spraying tip of the nozzle is inset by at least 25 mm and by no more than 40 mm into the outlet conduit.

5 Preferably also, the air-blowing means is provided with a source of steam whereby steam is additionally blown into the enclosed space through the outlet conduit.

Preferably also, the atomizing nozzle comprises a 60°

10 solid cone nozzle.

Preferably also, the spraying means is adapted is adapted to spray at least 11 litres of liquid per hour at a pressure of  $7 \times 10^5$  N per  $m^2$  (7 bar).

15

Preferably also, the air-blowing means comprises a cylindrical fan.

20 Preferably also, the apparatus is located in proximity to the ceiling at the top of a wall of the enclosed space.

The present invention will now be described by way of example with reference to the accompanying drawings, in which:-

25

Fig. 1 is a schematic diagram of a mist-spraying apparatus according to the present invention; and

30 Fig. 2 is a perspective view of the exterior of apparatus as shown in Fig. 1 when mounted within the storage area of a delivery vehicle.

A mist-spraying apparatus in accordance with the invention comprises an air-blowing means 1 and a spraying means 2. Preferably, as shown in Fig. 2 the apparatus is adapted to be located within a housing 3 that can be mounted

- 5 -

at a suitable site within an enclosed area, as partially shown in Fig. 2 and as further described below, and connected to a power source. Apparatus that is intended to be used within a vehicle can be adapted to be powered by the vehicle itself by being linked to the vehicle's batteries. Alternatively, it can be provided with its own battery power supply which is adapted to be re-charged when the vehicle is in motion. Alternatively, apparatus for use in buildings and other permanent or semi-permanent structures can be powered from a mains electricity supply.

With particular reference to Fig. 1, the air blowing means 1 comprises a fan 4 powered by a motor 5 and defines an outlet conduit 6 through which air can be blown into the space and an inlet conduit 7 covered by a grille through which air from within the space can be drawn for blowing through the outlet conduit 6 to circulate within the space. The fan 4 is preferably a cylindrical fan but any suitable blowing means can be employed. For example, a cylindrical fan which is 130 mm across is capable of delivering an airflow of between 1.4 and 1.7 m<sup>3</sup> per minute, which is suitable for use in an average-sized vehicle storage space with approximate dimensions of 12m by 3m by 3m (40' x 10' x 10').

The outlet conduit 6 is located at the front of the housing 3 and it has been found that an outlet conduit 6 with a rectangular cross-sectional profile provides an airflow pattern that is better at reaching all corners and exposed surfaces within spaces which are rectangular, parallelepipedal spaces than the airflow pattern provided by a circular outlet conduit. The outlet conduit 6 therefore defines a slot 8 so that the airstream emitted into the space is in the form of a slot-jet. The slot 8 preferably has dimensions of 85 mm by 70 mm when used to deliver an airflow as detailed above within the storage area of a delivery vehicle which is long and narrow, as shown in Fig. 2. In this



- 6 -

case the slot 8 is orientated with its longer sides vertical but these sides can be disposed horizontally for enclosed spaces which are wider than they are high. Also, the apparatus is preferably located in proximity to the ceiling at the top of a wall of the enclosed space, as shown in Fig. 2. This enables the apparatus to mist-spray the space effectively.

The spraying means 2 comprises a pump 9 for delivering liquid from a reservoir 10 to an atomizing nozzle 11 for spraying the liquid into the space in the form of an atomized mist. The atomizing nozzle 11 is located within the outlet conduit 6 so that atomized particles emitted by the atomizing nozzle are entrained in the airstream emitted by the fan 4 and thereby distributed evenly throughout the space. In order to obtain the most efficient dispersal of the atomized particles within the airstream, the atomizing nozzle 11 is located centrally within the outlet conduit 6 and preferably its spraying tip 12 is inset therein. It has been found that the spraying tip 12 should be inset by a distance  $l$  at least 25 mm but no more than 40 mm into the outlet conduit 6 to ensure that the atomized particles emitted therefrom are all entrained in the most efficient manner in the airstream. Also, the atomizing nozzle 11 preferably comprises a 60° solid cone nozzle. Typically, such a spraying means should be capable of spraying at least 11 litres of liquid per hour at a pressure of  $7 \times 10^5$  N per  $m^2$  (7 bar). Such a spraying rate is suitable for use in a vehicle storage space as detailed above.

30

A control means 13 is provided for controlling operation of the air-blowing means 1 and the spraying means 2 and is adapted to commence operation of the fan 4 prior to operation of the atomizing nozzle 11 and to continue operation of the fan 4 after operation of the nozzle 11 has ceased. This continues circulation of the air and any atomized particles

- 7 -

entrained therein around the space for a predetermined period of time, which may be several minutes, dependent on the size of the enclosed space being treated.

5        This arrangement has two advantages. First, when an atomizing nozzle is operated, the pump 9 switches on and during an very short initial period the pressure of the liquid being discharged by the nozzle 11 rises to a predetermined substantially constant level. During the period  
10 of time wherein the pressure is rising, the nozzle 11 tends to discharge liquid particles that are not fully atomized. However, these particles can be broken up and entrained fully into the airstream flowing past the nozzle 11 if the airstream has been established prior to operation of the  
15 nozzle. Likewise, when the pump 9 is switched off, the nozzle 11 tends to discharge liquid particles but again these can be broken up and entrained within the airstream if the airstream is continued at a constant level for a predetermined time thereafter.

20

Second, continuing to recirculate the air along with entrained particles within the space for a predetermined period even after the nozzle 11 has ceased operation, ensures that all exposed surfaces within the space are reached by the  
25 airstream and can be acted upon by the sprayed liquid.

The control means 13 is provided with an emergency stop button 14, for use in the unfortunate event that the apparatus is remotely operated whilst a person is trapped  
30 within the space. To reduce the chances of such an occurrence, the control means 13 is preferably provided with an audible alarm 15 which sounds continuously during operation of the apparatus. In addition, the control means 13 can be linked to locks on the doors of the space to prevent  
35 them being opened whilst the apparatus is in use.

- 8 -

In order to ensure that the reservoir 10 is always adequately filled with liquid to be sprayed, a float 16 is provided within the reservoir 10 and used to trigger an alarm by making electrical contact with, for example, a block 17 located at the base of the reservoir 10 and linked to the control means. When the level of the liquid in the reservoir becomes low, a flashing light, for example, or other alarm means can be triggered by the control means 13 to warn operatives that the reservoir 10 should be topped up.

The control means 13 can also incorporate or be linked to a recording means 18 which records the time and duration of each operation of the apparatus so that checks can be run to ensure that operatives are using the apparatus appropriately and adequately.

It will be appreciated that the apparatus as described herein can be readily adapted for use in various applications. The liquid being sprayed can also vary as required. For example, when spraying soiled laundry, the liquid can comprise a sanitizing liquid including biocides and disinfectants. Alternatively, if used for mist-spraying in glasshouses, the liquid may comprise a pesticide, fungicide, and/or a foliar feed.

In a modification of the above apparatus for particular use in a hospital operating theatre or an enclosed space wherein it is desired not only to sanitize exposed surfaces but also to treat air-borne particles, the air-blowing means 1 can be supplied with steam from a suitable source so that steam is additionally blown into the enclosed space. Other gaseous substances could also be supplied to the apparatus for spraying into the enclosed space along with or in place of the steam as appropriate for any particular use of the apparatus.

- 9 -

CLAIMS

1. A mist-spraying apparatus primarily but not exclusively for use in an enclosed space comprising

5

an air-blowing means with an outlet conduit through which air can be blown into the space and an inlet conduit through which air from within the space can be drawn for blowing through the outlet conduit to circulate within the space;

10

a spraying means comprising a pump for delivering liquid from a reservoir to an atomizing nozzle for spraying the liquid into the space in the form of an atomized mist, the atomizing nozzle being located within the outlet conduit so that atomized particles emitted by the atomizing nozzle are entrained in the airstream emitted by the air-blowing means and thereby distributed evenly throughout the space; and

15

20

25

a control means for controlling operation of the air-blowing means and the spraying means that is adapted to commence operation of the air-blowing means prior to operation of the atomizing nozzle and to continue operation of the air-blowing means after operation of the nozzle has ceased in order to continue circulation of the air and any atomized particles entrained therein around the space for a predetermined period of time.

30

2. An apparatus as claimed in Claim 1, wherein the atomizing nozzle is located centrally within the outlet conduit.

35

3. An apparatus as claimed in Claim 1 or Claim 2, wherein the outlet conduit has a rectangular cross-sectional profile.

- 10 -

4. An apparatus as claimed in any of Claims 1 to 3, wherein the outlet conduit defines a slot so that the airstream emitted into the space is in the form of a slot-jet.

5

5. An apparatus as claimed in any of Claims 1 to 4, wherein the atomizing nozzle is inset within the outlet conduit.

6. An apparatus as claimed in any of Claims 1 to 6, wherein a spraying tip of the nozzle is inset by at least 25 mm and by no more than 40 mm into the outlet conduit.

10

7. An apparatus as claimed in any of Claims 1 to 6, wherein the air-blowing means is provided with a source of steam whereby steam is additionally blown into the enclosed space via the outlet conduit.

15

8. An apparatus as claimed in any of Claims 1 to 7, wherein the atomizing nozzle comprises a 60° solid cone nozzle.

20

9. An apparatus as claimed in any of Claims 1 to 8, wherein the spraying means is adapted to spray at least 11 litres of liquid per hour at a pressure of 7 x 10<sup>5</sup> N per m<sup>2</sup> (7 bar).

25

10. An apparatus as claimed in any of Claims 1 to 9, wherein the air-blowing means comprises a cylindrical fan.

11. An apparatus as claimed in any of Claims 1 to 10, which is located in proximity close to the ceiling at the top of a wall of the enclosed space.

30

12. A mist-spraying apparatus primarily but not exclusively for use in an enclosed space substantially as described herein with reference to the accompanying drawings.

35


- 11 -

## ABSTRACT

## A MIST-SPRAYING APPARATUS

5        A mist-spraying apparatus primarily but not exclusively  
for use in an enclosed space comprises an air-blowing means  
(1), a spraying means (2) and a control means (13). The air-  
blowing means (1) defines an outlet conduit (6) through which  
air can be blown into the space and an inlet conduit (7)  
10 through which air from within the space can be drawn for  
blowing through the outlet conduit (6) to circulate within  
the space. The spraying means (2) comprises a pump (9) for  
delivering liquid from a reservoir (10) to an atomizing  
nozzle (11) for spraying into the space in the form of an  
15 atomized mist. The atomizing nozzle (11) is located within  
the outlet conduit (6) so that atomized particles emitted by  
the atomizing nozzle (11) are entrained in the airstream  
emitted by the air-blowing means (2) and thereby distributed  
evenly throughout the space. The control means (13) controls  
20 operation of the air-blowing means (1) and the spraying means  
(2) and is adapted to commence operation of the air-blowing  
means (1) prior to operation of the atomizing nozzle (11) and  
to continue operation of the air-blowing means (1) after  
operation of the nozzle (11) has ceased in order to continue  
25 circulation of the air and any atomized particles entrained  
therein around the space for a predetermined period of time.

1/2



**Fig. 1**

2/2




Fig. 2



**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record.**

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☒ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☒ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☒ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**